



The Canadian reference for hydraulic dock levelers

All Pro-dock hydraulics dock levelers are designed with central support for three-wheeled forklift trucks as well as piano type front and rear hinges, made of solid tubes and bars, designed to maintain superior structural integrity without reducing lateral bending capabilities.

Complete hydraulic dock leveler system assembled at the factory, including:

- *Main cylinder (two for the 80k lb capacity and higher).*
- *Double action cylinder on the lip (two for the 80k lb capacity and higher).*
- *1 HP power unit (1,5 HP for 4 cylinders models).*

- *Electrical control box ready for installation by your electrician and offered for the majority on conventional voltage.*
- *A velocity fuse in case of an unexpected drop of the leveler.*

Standard dimensions:

- *6' or 7' wide*
- *6', 8', 10' or 12' long*
- *30 000 lb to 120 000 lb Dynamic load capacity*
- *12" Working height*

Standard equipment:

- *Working range toe-guard.*
- *Maintenance stand.*
- *16" Lip (18" for capacities of 60 000 lb and more).*

Optional equipment for a hydraulic dock leveler:

- *18" or 20" Lip.*
- *Neoprene lateral weather seal.*
- *Brush-type lateral weather seal.*
- *Full range toe-guard.*
- *Safety lip.*
- *Wall-mounted power unit.*
- *Dock auto-return.*
- *Full control NEMA 12 dock with interlock.*
- *Clean-frame-type design.*
- *Urethane insulated deck.*
- *Galvanised dock leveler.*
- *Other options are available upon request.*